PR 100,000 CST SILICONE FLUID Safety Data Sheet

Section 1-Chemical Product and Company Identification

Company Information:

 PremierRepak Inc.
 Phone: (708) 444-2688

 8351 W. 185th Street
 Fax: (708) 429-4280

Tinley Park, IL 60487

InfoTrac 24-hour Emergency Phone Number: 1 (800) 535-5053

InfoTrac Contract Number: 105384

Product Information:

Substance/Mixture: Substance

Substance name: Dimethyl siloxane, trimethylsiloxy-terminated: C.A.S. Number: 63148-62-9

Chemical nature: Silicone Recommended use: Cosmetics

Section 2-Hazard Identification

GHS Classification: Not a hazardous substance or mixture.

GHS Label element: Not a hazardous substance or mixture.

Precautionary Statements:

Prevention:

P261: Avoid breathing spray.

P271: Use only outdoors or in a well-ventilated area.

Other hazards: None known.

Section 3-Composition and Information on Ingredients

Hazardous Ingredients:

Common Name C.A.S. No. Wt. %

NONE

Section 4 – First Aid Measures

If inhaled: Remove to fresh air. Get medical attention if symptoms occur.

In case of skin contact: Wash with water and soap as a precaution. Get medical attention if symptoms

occur.

In case of eye contact: Flush eyes with water as a precaution. Get medical attention if irritation

develops and persists.

If swallowed: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur.

Document: SDS-PRSF-100000CST Revision Date: 2015/06/08

Revision Date: 2015/06/0/ Revision #: 3

Page 1 of 10



PR 100,000 CST SILICONE FLUID Safety Data Sheet

Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed: None known

Protection of first-aiders: No special precautions are necessary for first aid responders.

Notes to physician: Treat symptomatically and supportively.

Section 5- Firefighting Measures

Suitable extinguishing media: Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO2)

Unsuitable extinguishing media: Not known

Specific hazards during firefighting: Exposure to combustion products may be a hazard to health.

Hazardous combustion products: Carbon oxides, Silicon oxides, Formaldehyde.

Specific extinguishing methods: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for fire fighters: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions:

Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages cannot be contained.

Prevent spreading over a wide area (e.g. by containment or oil barriers).

Methods and materials for containment and cleaning up:

Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

Document: SDS-PRSF-100000CST Revision Date: 2015/06/08

Revision #: 3 Page 2 of 10

PR 100,000 CST SILICONE FLUID Safety Data Sheet

Section 7- Handling and Storage

Technical measures:

See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section

Local/Total ventilation:

Use with local exhaust ventilation.

Advice on safe handling:

Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage:

Keep in properly labeled containers. Store in accordance with the particular national regulations.

Materials to avoid:

Do not store with the following product types:

Strong oxidizing agents

Section 8- Exposure Controls and Personal Protection

Hazardous Component with workplace control parameters:

		Value type	Control parameters	
Common Name	C.A.S. No.	(Form of exposure)	Permissible Conc.	<u>Basis</u>

Contains NO substances with occupational exposure limit

Hazardous Component without workplace control parameters:

Common Name	C.A.S. No.

NONE

Occupational exposure limits of decomposition products:

		value type	Control parameters	
Common Name	C.A.S. No.	(Form of exposure)	Permissible Conc.	<u>Basis</u>

NONE

Engineering measures:

Processing may form hazardous compounds (see section 10). Minimize workplace exposure concentrations. Ensure adequate ventilation, especially in confined areas.

Document: SDS-PRSF-100000CST Revision Date: 2015/06/08 Revision #: 3

Page 3 of 10

PR 100,000 CST SILICONE FLUID Safety Data Sheet

Personal protective equipment:

Respiratory protection: No personal respiratory protective equipment normally required.

Hand protection:

Remarks: Wash hands before breaks and at the end of workday.

Eye protection: Wear the following personal protective equipment: Safety glasses

Skin and body protection: Skin should be washed after contact.

Hygiene measures:

Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before reuse. These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Premier Repak customer service group.

Section 9- Physical/Chemical Characteristics

Odor: characteristic Appearance: viscous liquid
Odor Threshold: No data available Color: Colorless

Odor Threshold: No data available
Freezing/Melting Point: No data available.
Initial Boiling Point: >65 degrees Celsius
Vapor Pressure: No data available.
Vapor Density: No data available.

Solubility in Water: No data available. **pH**: No data available.

Volatile Content: Not determined.

Flash Point: >321.11 °C Method: closed cup Auto ignition Temperature: No data available. Flammability (solid, gas): Not applicable Evaporation rate: No data available Upper explosion limit: No data available Lower explosion limit: No data available

Partition coefficient: noctanol/water: No data available

Decomposition temperature: No data available

Viscosity, kinematic: 100,000 cSt Explosive properties: Not explosive

Oxidizing properties: The substance or mixture is not classified as oxidizing.

Molecular weight: No data available

Relative Density: 0.97

Section 10- Stability and Reactivity

Reactivity: Not classified as a reactivity hazard.

Document: SDS-PRSF-100000CST Revision Date: 2015/06/08

Revision #: 3 Page 4 of 10

PR 100,000 CST SILICONE FLUID Safety Data Sheet

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions:

Can react with strong oxidizing agents. When heated to temperatures above 150 °C (300 °F) in the presence of air, trace quantities of formaldehyde may be released. Adequate ventilation is required. See OSHA formaldehyde standard, 29 CFR 1910.1048 Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid: Not Known

Incompatible materials: Oxidizing agents

Hazardous decomposition products:

Thermal decomposition: Formaldehyde

Section 11- Toxicological Information

Information on likely routes of exposure:

Skin contact Ingestion Eye contact Inhalation

Acute toxicity:

Not classified based on available information.

Product:

Oral:

Acute toxicity: LD50 (Rat): > 15,400 mg/kg

Assessment: The substance or mixture has no acute oral toxicity

Remarks: Based on data from similar materials.

Dermal:

Acute toxicity: LD50 (Rabbit): < 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal toxicity

Remarks: Based on data from similar materials.

Skin corrosion/irritation:

Not classified based on available information.

Product:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

Serious eye damage/eye irritation:

Not classified based on available information.

Document: SDS-PRSF-100000CST Revision Date: 2015/06/08

Revision #: 3 Page 5 of 10



PR 100,000 CST SILICONE FLUID Safety Data Sheet

Product:

Species: Rabbit **Result:** No eye irritation

Remarks: Based on data from similar materials

Respiratory or skin sensitization:

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

Test Type: Maximization Test (GPMT)

Species: Guinea pig

Remarks: No known sensitizing effect. Based on data from similar materials.

Germ cell mutagenicity;

Not classified based on available information.

Product:

Genotoxicity in vitro:

Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials.

Carcinogenicity:

Not classified based on available information.

Product:

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity Assessment: Animal testing did not show any carcinogenic

effects.

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Document: SDS-PRSF-100000CST Revision Date: 2015/06/08

Revision #: 3 Page 6 of 10

PR 100,000 CST SILICONE FLUID Safety Data Sheet

Reproductive toxicity:

Not classified based on available information.

Product:

Effects on Fertility:

Test Type: Reproduction/Developmental toxicity screening test

Species: Rabbit, male
Application Route: Ingestion
Symptoms: No effects on fertility.

Remarks: Based on data from similar materials

Effects on fetal development:

Test Type: Reproduction/Developmental toxicity screening test

Species: Rabbit, male

Application Route: Ingestion

Symptoms: No effects on fetal development. **Remarks:** Based on data from similar materials

Test Type: Prenatal development toxicity study (teratogenicity)

Species: Rabbit, female

Application Route: Skin contact

Symptoms: No effects on fetal development. **Remarks:** Based on data from similar materials

Reproductive Assessment: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

STOT-single exposure:

Not classified based on available information.

STOT-repeated exposure:

Not classified based on available information.

Product:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations

of 100 mg/kg bw or less.

Routes of exposure: Skin contact

Assessment: No significant health effects observed in animals at concentrations

of 200 mg/kg bw or less.

Repeated dose toxicity:

Product:

Species: Rat

Application Route: Ingestion Remarks: Based on test data

Document: SDS-PRSF-100000CST Revision Date: 2015/06/08

Revision #: 3 Page 7 of 10



PR 100,000 CST SILICONE FLUID Safety Data Sheet

Species: Rabbit

Application Route: Skin contact

Remarks: Based on data from similar materials

Aspiration toxicity:

Not classified based on available information.

Product: No aspiration toxicity classification.

Section 12 - Ecological Information

Ecotoxicity: No data available

Persistence and degradability: No data available

Bioaccumulative potential: No data available

Mobility in soil: No data available

Other adverse effects: No data available

Section 13 – Disposal Considerations

Disposal methods:

Resource Conservation and Recovery Act (RCRA): This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues: Dispose of in accordance with local regulations.

Contaminated packaging:

Dispose of as unused product. Empty containers should be taken to an approved waste-handling site for recycling or disposal.

Section 14 – Transport Information

International Regulation:

UNRTDG: Not regulated as a dangerous good **IATA-DGR:** Not regulated as a dangerous good **IMDG-Code:** Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:

Not applicable for product as supplied.

Domestic regulation:

49 CFR: Not regulated as a dangerous good

Document: SDS-PRSF-100000CST Revision Date: 2015/06/08

Revision #: 3 Page 8 of 10

PR 100,000 CST SILICONE FLUID Safety Data Sheet

Section 15- Hazard Classification

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity:

Component Name CAS Number Component RQ (lbs) Calculated product RQ(lbs)

NONE

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity:

Component Name CAS Number Component RQ (lbs) Calculated product RQ(lbs)

NONE

SARA 311/312 Hazards: NONE

<u>SARA 302:</u> No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

<u>SARA 313:</u> This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations:

California:

Warning: This product does NOT contain the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

Component Name CAS Number

NONE

State Right-To-Know:

CAS Number	Wt %	Component Name	State
63148-62-9	90 - 100 %	Dimethyl siloxane,	New Jersey,
		trimethylsiloxy-terminated	Pennsylvania

The ingredients of this product are reported in the following inventories:

AICS: All ingredients listed or exempt.

DSL: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

REACH: All ingredients (pre-) registered or exempt.

IECSC: All ingredients listed or exempt.

Document: SDS-PRSF-100000CST Revision Date: 2015/06/08

Revision #: 3 Page 9 of 10

PR 100,000 CST SILICONE FLUID Safety Data Sheet

ENCS/ISHL: All components are listed on ENCS/ISHL or exempted from inventory listing. **KECI:** All ingredients listed, exempt or notified.

Inventories:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

Section 16 - Other Information

Further information:

NFPA: HMIS III:

Flammability: 1 Flammability: 1 Health: 0 Health: 0 Physical Hazard: 0

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

Product: PR 100,000 CST Silicone Fluid

Sources of key data used to compile the Safety Data Sheet:

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/

Prepared by: PremierRepak, Inc.

Special hazard: None

http://premierrepak.com/

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

Document: SDS-PRSF-100000CST Revision Date: 2015/06/08

Revision #: 3 Page 10 of 10