

PR1009

General Purpose Transparent Spray PTFE Gel

GENERAL INFORMATION: *PR1009 General Purpose Transparent Spray PTFE Gel* is a transparent, high pressure lubricant with high adhesive strength. A unique combination of natural and synthetic lubrication agents coupled with a high molecular weight polymer (Polytetrafluoroethylene or PTFE) makes this product one of the best lubricants available.

PRODUCT DESCRIPTION: *PR1009 General Purpose Transparent Spray PTFE Gel* features high adhesive strength, quickly evaporating solvents, and it continues to lubricate over a wide temperature range.

PR1009 General Purpose Transparent Spray PTFE Gel adheres to surfaces, and resists throw-off squeeze out when subjected to high pressures, vibrations, or repeated impact. It allows maximum penetration and rapid set up of the grease-like lubricant. *PR1009 General Purpose Transparent Spray PTFE Gel* will withstand high temperatures without melting, has a high dropping point and helps prevent rust and corrosion.

PHYSICAL PROPERTIES:

Appearance:	Clear
Odor:	Solvent
Propellant:	Hydrocarbon
V.O.C.	63%
NFPA 714 – Flammability	4
NFPA 30B – Storage	3
Service Temperature:	-30°F to 550°F

APPLICATION: Door hinges, open gears, wire ropes and cables, chains and sprockets, conveyors, manifold heat valves, and above water line marine applications.

DIRECTIONS FOR USE: Shake can well before using. Saturate area to be lubricated and allow solvent to evaporate. Use an extension tube for hard to reach areas.

IMPORTANT NOTICE: All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. PremierRepak, Inc. is not responsible for loss, claim or damages resulting from use of its products.