

PR7703

Nickel Based Anti-Seize Paste

GENERAL INFORMATION: *PR7703 Nickel Based Anti-Seize Paste* provides ultimate protection as a high temperature anti-seize and extreme pressure lubricant. *PR7703 Nickel Based Anti-Seize Paste* stops corrosion, galling and seizure between metal parts and it performs to 2600°F.

PRODUCT DESCRIPTION: *PR7703 Nickel Based Anti-Seize Paste* is a smooth, non-separating formula consisting of a lithium soap thickened grease into which is compounded very fine metallic particles of pure nickel and aluminum as well as graphite lubricants and corrosion fighting inhibitors. This high performance grease and solid additives provide extreme pressure lubricating properties that prevent galling and cold welding and at the same time prevent water wash out and galvanic pitting from electrolysis of road salt, acid rain or salt water. *PR7703 Nickel Based Anti-Seize Paste* is non-hardening and has exceptional thermal stability. The particles present are inert and will not evaporate at extreme temperatures and their heat resistant qualities will prevent carbon fusion and seizure at temperatures approaching 2600°F.

PRODUCT CHARACTERISTICS: (Paste)

Color	Silver Gray
NLGI	1
Flash Point C.O.C.	500°F
Penetration @ 77°F:	270 ± 20
Temperature Range	-65 to 2600°F
Specific Gravity	1.2
Weight per gallon	10.3 lbs.
Drop Point	380°F
Particle Size	1 Mil Maximum
Coefficient of Friction	0.085 (Shell 4 Ball Method)

APPLICATION: This product is recommended where very different metals are used together such as brass and steel because Nickel is a hard metal and keeps surfaces apart. It is also used where high Nickel alloy metals such as stainless steel, or where Titanium or other hard metals are involved. *PR7703 Nickel Based Anti-Seize Paste* is also used where metals such as copper cannot be present, such as in caustic, ammonium or high acidity processing plants. Surfaces need not be cleaned before application unless grit or low quality oil/grease is present and ultimate performance is required. Use on threaded parts, bushings, gears, valve systems, chains, sprockets, levers, hinges, pivots, rollers, heat exchanger or manifold bolts, or as a gasket release agent, etc.

NOTE: This product is not recommended for pure oxygen systems.

IMPORTANT NOTICE: All statements and technical data contained herein are based on tests we believe to be reliable, but the accuracy of completeness thereof is not guaranteed. It is recommended that the buyer test this product to determine its suitability for his application before use. PremierRepak, Inc. is not responsible for loss, claim or damages resulting from use of its products.